



Zinc Plated Steel



Stainless Steel



Drive Unit

Internally Threaded Socket

SOCKET TYPE	SOCKET OVERALL LENGTH (mm)	HOLE DIAMETER IN CONCRETE (mm)	HOLE DEPTH IN CONCRETE (mm)	MINIMUM HOLE DIA. IN FIXTURE (mm)	USE WITH CAPSULE NUMBER	TIGHTENING TORQUE		PRODUCT CODE		
						30N/mm ² CONCRETE	20.5N/mm ² BRICKWORK	ZINC PLATED	STAINLESS STEEL GRADE 303 (A2)	DRIVE SYSTEM
M6 x 24	75	12	75	7	R-CAS 10	5	3	60-620	-	60-690
M6 x 24	75	14	75	7	R-CAS 10	5	3	-	60-985	60-690
M8 x 25	90	14	90	9	R-CAS 12	11	6	60-623	60-988	60-692
M10 x 30	100	20	100	11	R-CAS 16	22	13	60-626	60-991	60-694
M12 x 35	100	20	100	13	R-CAS 16	38	21	60-628	-	60-696
M12 x 35	100	22	100	13	R-CAS 16	38	21	-	60-993	60-696
M16 x 50	125	28	125	17	R-CAS 20	95	30	60-630	60-995	60-698



Brushes and Blow Pump

HOLE SIZE BRUSHES	PACK	QUANTITY	PRODUCT CODE
M8-10mm	Polybag	1	60-980
M10-14mm	Polybag	1	60-981
M16-28mm	Polybag	1	60-982
Blow Pump	Polybag	1	60-687