

# Fibre Plug

## Typical Applications:

- Fixing shelves and brackets.
- Installing wall lighting fixtures.




1. Tough and elastic natural fibrous material ensures a firm grip.
2. Screw cuts its own thread and expands the plug without damage.

- The original, handy all purpose fixing for brickwork, blockwork and concrete.
- Available in a range of useful sizes.


## Product Specification

| DESC.         | SCREW SIZE (mm) | HOLE DIA. (mm) | PLUG LENGTH (mm) | FIXINGS PER PACK |     | BOX PRODUCT CODE |
|---------------|-----------------|----------------|------------------|------------------|-----|------------------|
|               |                 |                |                  | RETAIL           | BOX |                  |
| No. 8 x 1"    | 4.5             | 4.5            | 25, 38           | -                | 100 | 01-022           |
| No. 8 x 1.5"  | 4.5             | 4.5            | 25, 38           | -                | 100 | 01-026           |
| No. 10 x 1.5" | 5               | 5.5            | 38, 50           | -                | 100 | 01-038           |
| No. 10 x 2"   | 5               | 5.5            | 38, 50           | -                | 100 | 01-040           |
| No. 12 x 1.5" | 5.5             | 6.5            | 38, 50           | -                | 100 | 01-048           |
| No. 12 x 2"   | 5.5             | 6.5            | 38, 50           | -                | 100 | 01-050           |
| No. 14 x 2"   | 6               | 7              | 50               | -                | 100 | 01-056           |
| Assorted      | -               | -              | -                | 25               | -   | -                |


## Installation



1. Drill hole to indicated diameter and depth of plug.



2. Insert plug and tap home.



3. Place fixture in position. Insert screw and tighten until secure.



# RawInut™ Flexi-Plug

- A problem solving fixing suitable for use in virtually any construction material, solid or hollow.



1. Resistant to vibration and corrosion.
2. Flange holds fixing flush to wall surface.
3. Sleeve compresses to provide secure fixing, even in irregular shaped holes.
4. Made from synthetic rubber for more severe conditions.
5. Bonded brass insert.

## Typical Applications:


- Fixing to virtually any material, either solid or hollow, eg metal sheet, car panels, thin panel, plasterboard, plywood, glass, plastic, etc.
- Secure fixing in brittle or unknown substrates.
- Ideal for fixing in irregular or oversized holes.

## Product Specification


| DESC.    | SCREW LENGTH (mm) | HOLE DIA. (mm) | FLANGE THICKNESS (mm) | LENGTH (mm) | GRIP RANGE (mm) | FIXINGS PER PACK |     | BOX PRODUCT CODE |
|----------|-------------------|----------------|-----------------------|-------------|-----------------|------------------|-----|------------------|
|          |                   |                |                       |             |                 | RETAIL           | BOX |                  |
| *3240 M3 | 30                | 8              | 1.2                   | 24.0        | 6-14            | 4                | 50  | 09-040           |
| *4100 M4 | 20                | 8              | 1.4                   | 12.6        | 0-4             | 4                | 50  | 09-100           |
| *4240 M4 | 30                | 8              | 1.2                   | 24.0        | 6-14            | -                | 50  | 09-130           |
| *5150 M5 | 20                | 10             | 0.9                   | 14.1        | 0-5             | -                | 50  | 09-195           |
| *5250 M5 | 30                | 10             | 1.3                   | 26.1        | 8-16            | 4                | 50  | 09-235           |
| *5400 M5 | 50                | 10             | 1.3                   | 39.8        | 20-30           | -                | 50  | 09-317           |
| 6150 M6  | -                 | 13             | 1.3                   | 16.0        | 0-3             | -                | 50  | 09-355           |
| 6250 M6  | -                 | 13             | 2.0                   | 26.7        | 6-26            | -                | 50  | 09-385           |
| 6350 M6  | -                 | 13             | 1.3                   | 35.0        | 11-23           | -                | 50  | 09-415           |
| 8250 M8  | -                 | 16             | 5.0                   | 27.9        | 4-10            | -                | 50  | 09-473           |
| 8300 M8  | -                 | 18             | 1.2                   | 30.0        | 6-15            | -                | 50  | 09-475           |
| 8500 M8  | -                 | 18             | 2.0                   | 50.0        | 15-39           | -                | 50  | 09-533           |
| 1055 M10 | -                 | 20             | 1.3                   | 55.0        | 20-36           | -                | 25  | 09-594           |
| 1275 M12 | -                 | 24             | 1.3                   | 80.0        | 30-50           | -                | 20  | 09-654           |

\*Also available without screws.


## Installation




1. Drill appropriate diameter hole. For solid materials, drill hole to length of screw. Clean out hole and remove sharp edges to avoid damaging fixing.



2. Insert the fixing up to its flange.



3. Place fixture in position. Insert screw and tighten to compress sleeve and form a secure fixing. Do not overtighten.



4. Works equally well in uniform or irregularly shaped holes.